

PUREZZA™

PREMIUM WATER

EXL65HC

High performance cellar-fed system for the HORECA sector.



*Purezza tap required with cellar-fed systems

High capacity cellar-fed system

Built for durability and reliability, the EXL65HC achieves optimum dispense-point temperatures by combining its efficient refrigeration system with a unique and optimised coil-pack design.

The EXL65HC Cooler Carbonator pairs elegantly with our Purezza tap to provide filtered chilled still and sparkling water time after time.

The EXL65HC features three core technologies:



Performance filtration

Professional grade filters are used to improve taste and reduce odours resulting in great-tasting, crystal-clear ice.



Ice Bank cooling technology

Ice Bank cooling technology is a necessity in busy HORECA environments where large quantities of consistently ice-cold water are required.



Professional water dispensing for commercial environments

EXL65HC is the recommended cellar-fed solution for HORECA environments such as bars, restaurants, cafés, hotels and conference centres. Perfect for areas with limited front of house space.



Features

Designed specifically for cellar installations.

High capacity cellar unit paired with elegant Purezza bar tap.

Two water dispensing options – cold and sparkling.

Re-circulating technology, ensures constant 'in line' cold temperature is maintained, ensuring optimum sparkling water.

Practical mechanical taps allows two Purezza bottles to be filled at the same time.

Tap surfaces designed in stainless steel to facilitate easy cleaning.

Purezza 'still' and 'sparkling' tap decals to promote Purezza within your venue



Tap Drip Tray Options

Recessed drip tray
Tap clamp drip tray
Free standing drip tray

Cutting templates all available upon request

Tested and certified



Waterlogic International Limited reserves the right, in order to reflect continuous research and development, to amend or change specifications without prior notice.

Technical specifications

Dimensions

655mm (W) x 299mm (H) x 455mm (D)

Weight Dry / Installed

36kg/ 55kg

Dispensing Capacity

90L

Dispensing Area

286mm (work surface)

325mm (tap clamp)

Power Required

230V / 50Hz

Max Power Consumption

350w

Refrigerant

R290 (65g)

Water Temperature

6°C-10°C

Water options

cold



sparkling



Contact the Purezza team today

Purezza UK

0333 323 2735

enquiries@purezza-water.co.uk

For more information, visit
www.purezza-water.co.uk